

Per-Fix™ for Vinyl

according to the Hazardous Products Regulations (February 11, 2015)

SECTION 1 - IDENTIFICATION

1.1 Product Identifier

Product Name : Per-Fix™ for Vinyl
 Manufacturer Product Number : 6405AAA, 6405AA, 6405A, 6405B, 6405C

1.2 Other Means of Identification

Other Identifiers : Flaw Repair

1.3 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended Use : Touch-up coating for molded plastic parts.
 Restrictions on Use : None Identified

1.4 Supplier Details

	Manufacturer Details	Supplier Details
Company Name	Chem-Pak Inc	Chem-Pak Inc
Address	242 Corning Way, Martinsburg, WV 25405 - United States	242 Corning Way, Martinsburg, WV 25405 - United States
Phone Number	304-262-1880	304-262-1880
Fax Number	304-262-9643	304-262-9643
Email	msds@chem-pak.com	
Website	http://www.chem-pak.com	

1.5 24 hr Emergency Phone Number

Emergency Number : ChemTel: 800-255-3924 (North America)

SECTION 2 - HAZARDS IDENTIFICATION

2.1 Classification of the Substance or Mixture

Flam. Liq. 2	H225	Physical Hazards	Flammable liquids, Category 2
Skin Irrit. 2	H315	Health Hazards	Skin corrosion/irritation, Category 2
Eye Irrit. 2	H319	Health Hazards	Serious eye damage/eye irritation, Category 2
Muta. 1	H340	Health Hazards	Germ cell mutagenicity, Category 1
Carc. 1	H350	Health Hazards	Carcinogenicity, Category 1
Repr. 2	H361	Health Hazards	Reproductive toxicity, Category 2
Stot Se 3	H336	Health Hazards	Specific target organ toxicity — Single exposure, Category 3, Narcosis
Stot Re 2	H373	Health Hazards	Specific target organ toxicity — Repeated exposure, Category 2
Asp. Tox. 1	H304	Health Hazards	Aspiration hazard, Category 1
Aquatic Acute 3	H402	Environmental Hazards	Hazardous to the aquatic environment — Acute Hazard, Category 3

2.2 Label Elements

Hazard Pictograms



GHS02



GHS07



GHS08

Signal Word

Danger

Hazard Statements

H225 : Highly flammable liquid and vapour.
 H304 : May be fatal if swallowed and enters airways.
 H315 : Causes skin irritation.
 H319 : Causes serious eye irritation.
 H336 : May cause drowsiness or dizziness.

Per-Fix™ for Vinyl

according to the Hazardous Products Regulations (February 11, 2015)

Precautionary Statements	<p>H340 : May cause genetic defects. H350 : May cause cancer. H361 : Suspected of damaging fertility or the unborn child. H373 : May cause damage to organs through prolonged or repeated exposure. H402 : Harmful to aquatic life</p> <p>P202 : Do not handle until all safety precautions have been read and understood. P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 : Keep container tightly closed. P240 : Ground/bond container and receiving equipment. P241 : Use explosion-proof electrical/ventilating/lighting equipment. P242 : Use only non-sparking tools. P243 : Take action to prevent static discharges. P260 : Do not breathe vapour or fumes. P264 : Wash hands thoroughly after handling. P271 : Use only outdoors or in a well-ventilated area. P273 : Avoid release to the environment. P280 : Wear protective gloves and eye protection. P301+P310 : IF SWALLOWED: Immediately call POISON CENTER. P303+P361+P353 : IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water water. P304+P340 : IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 : If exposed or concerned: Get medical advice/attention P314 : Get medical advice/attention if you feel unwell. P331 : Do NOT induce vomiting. P332+P313 : If skin irritation occurs: Get medical advice/attention. P337+P313 : If eye irritation persists: Get medical advice/attention. P362+P364 : Take off contaminated clothing and wash it before reuse. P370+P378 : In case of fire: Use water, CO2, dry chemical, or universal aqueous film forming foam to extinguish. P403+P233 : Store in a well-ventilated place. Keep container tightly closed. P235 : Keep cool. P405 : Store locked up. P501 : Dispose of contents/container to applicable regulations</p>
---------------------------------	--

2.3 Other Hazards Which Do Not Result In Classification

Hazards Not Otherwise Classified : None Identified.

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substance / Mixture

Substance / Mixture : Mixture

3.2 Composition

Substance name	CAS Number	% wt*	Classification
Ethyl Acetate	141-78-6	30 - 60	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Methyl Ethyl Ketone	78-93-3	10 - 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

Per-Fix™ for Vinyl

according to the Hazardous Products Regulations (February 11, 2015)

Substance name	CAS Number	% wt*	Classification
Xylene	1330-20-7	10 - 30	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Light Aromatic Solvent Naphtha	64742-95-6	1 - 5	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Acute 3, H402
Ethylbenzene	100-41-4	1.7579	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
1,2,4-Trimethyl Benzene	95-63-6	1 - 5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Methyl Acetate	79-20-9	1 - 5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Toluene	108-88-3	0.1 - 1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Cumene	98-82-8	0.1 - 1	Flam. Liq. 3, H226 Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16
**Chemical name, CAS number and/or exact concentration have been withheld as a trade secret*

SECTION 4 - FIRST-AID MEASURES

4.1 Description of First-Aid Measures

General Measures	: Call a physician immediately.
Inhalation	: Remove person to fresh air and keep comfortable for breathing.
Skin Contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
Eye Contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	: Do not induce vomiting. Call a physician immediately.
First-Aid Responder Protection	: Wear adequate personal protective equipment based on the nature and severity of the emergency.

Per-Fix™ for Vinyl

according to the Hazardous Products Regulations (February 11, 2015)

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms of Exposure	: Eye Irritation, Nose Irritation, Throat Irritation, Dermatitis, Confusion, Skin Irritation, Headache, Dizziness, Nausea, Narcosis, Drowsiness, Vomiting, Optical Nerve Damage, Cough, Chest Tightness, Mucous Membrane, Diarrhea.
Delayed Effects	: No known delayed effects.
Immediate Effects	: No known immediate effects.
Chronic Effects	: Repeated or prolonged contact may cause skin sensitization.
Target Organs	: Central Nervous System, Eyes, Liver, Nasal Cavity, Reproductive System, Respiratory System, Skin, Kidneys.

4.3 Indication of Immediate Medical Attention and Special Treatment

Notes to Physician	: Treat symptomatically.
Specific Treatments/Antidotes	: No Information Available.
Medical Conditions Aggravated	: May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

SECTION 5 - FIRE-FIGHTING MEASURES

5.1 Suitable Extinguishing Media

Extinguishing Media	: Water, carbon dioxide, dry chemical, universal aqueous film forming foam.
Unsuitable Media	: Water jet.

5.2 Specific Hazards Arising from the Chemical or Mixture

Hazardous Combustion Products	: Decomposition products may include: oxides of carbon, smoke, vapours. See also Section 10.6.
Specific Hazards During Firefighting	: CONTENTS HIGHLY FLAMMABLE. In a fire or if heated, a pressure increase will occur which may result in container bursting. Vapours heavier than air may spread along the ground and travel to an ignition source.

5.3 Special Protective Actions for Fire-Fighters

Firefighting Instructions	: Use water spray to cool fire exposed containers, as contents can rupture violently from heat developed pressure.
Protection during Firefighting	: Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel	: No action should be taken involving any personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.
For Emergency Personnel	: Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel above.

6.2 Environmental Precautions

Environmental Precautions	: Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.
---------------------------	---

6.3 Methods and Materials for Containment and Cleaning up

Containment Procedures	: Released content may be contained with oil/solvent absorbent pads, booms, and/or absorbents.
Cleanup Procedures	: Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.
Other Information	: The North American Emergency Response Guidebook or similar resources providing emergency response information for dealing with accidents, spills, leaks, and/or fires involving dangerous goods.
Prohibited Materials	: Combustible absorbent material such as sawdust. Use of equipment that may cause sparking.

SECTION 7 - HANDLING AND STORAGE



SAFETY DATA SHEET

Part No. See Section 1.1 (Liquid)

Print Date: 10/10/2019
 Revision Date: 10/10/2019
 Supersedes Date: 10/10/2019
 Issue Date: 10/10/2019
 Version: 1.0 (EN)-CA
 Page: 5/12

Per-Fix™ for Vinyl

according to the Hazardous Products Regulations (February 11, 2015)

7.1 Precautions for Safe Handling

- General Handling Precautions** : KEEP OUT OF THE REACH OF CHILDREN. Avoid use around open flames or other sources of ignition.
- Hygiene Recommendations** : Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

7.2 Conditions for Safe Storage Including Any Incompatibilities

- Storage Requirements** : Storage of flammable materials should conform to NFPA 30 Flammable and Combustible Liquid. Keep containers tightly closed and stored in a well-ventilated place. Keep away from sources of ignition. . Keep containers closed when not in use. Do not store in open or unlabelled containers.

- Incompatibilities** : Segregate storage away from materials indicated in Section 10.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control Parameters

Ethyl Acetate (141-78-6)

Canada (Alberta)	OEL TWA (ppm)	400 ppm
Canada (Alberta)	OEL TWA (mg/m ³)	1440 mg/m ³
Canada (British Columbia)	OEL TWA (ppm)	150 ppm
Canada (Ontario)	OEL TWA (ppm)	400 ppm
Canada (Quebec)	VEMP (ppm)	400 ppm
Canada (Quebec)	VEMP (mg/m ³)	1440 mg/m ³
USA (ACGIH)	ACGIH TWA (mg/m ³)	400 ppm

Methyl Ethyl Ketone (78-93-3)

Canada (Alberta)	OEL TWA (ppm)	200 ppm
Canada (Alberta)	OEL TWA (mg/m ³)	590 mg/m ³
Canada (Alberta)	OEL STEL (ppm)	300 ppm
Canada (Alberta)	OEL STEL (mg/m ³)	885 mg/m ³
Canada (British Columbia)	OEL TWA (ppm)	50 ppm
Canada (British Columbia)	OEL STEL (ppm)	100 ppm
Canada (Ontario)	OEL TWA (ppm)	200 ppm
Canada (Ontario)	OEL STEL (ppm)	300 ppm
Canada (Quebec)	VECD (ppm)	100 ppm
Canada (Quebec)	VECD (mg/m ³)	300 mg/m ³
Canada (Quebec)	VEMP (ppm)	50 ppm
Canada (Quebec)	VEMP (mg/m ³)	150 mg/m ³
USA (ACGIH)	ACGIH TWA (mg/m ³)	200 ppm
USA (ACGIH)	ACGIH Ceiling (mg/m ³)	300 ppm
Biological Exposure Index	MEK in Urine, End of shift	2 mg/l

Toluene (108-88-3)

Canada (Alberta)	OEL TWA (ppm)	50 ppm
Canada (Alberta)	OEL TWA (mg/m ³)	188 mg/m ³
Canada (British Columbia)	OEL TWA (ppm)	20 ppm
Canada (Ontario)	OEL TWA (ppm)	20 ppm
Canada (Quebec)	VEMP (ppm)	50 ppm
Canada (Quebec)	VEMP (mg/m ³)	188 mg/m ³
USA (ACGIH)	ACGIH TWA (mg/m ³)	20 ppm
USA (ACGIH)	ACGIH Ceiling (mg/m ³)	150 ppm
Biological Exposure Index	Toluene in blood, Prior to last shift of workweek	0.02 mg/l
Biological Exposure Index	Toluene in urine, End of shift	0.03 mg/l
Biological Exposure Index	o-Cresol in urine (with hydrolysis), End of shift (B)	0.3 mg/g creatinine

Xylene (1330-20-7)

Canada (Alberta)	OEL TWA (ppm)	100 ppm
Canada (Alberta)	OEL TWA (mg/m ³)	434 mg/m ³
Canada (British Columbia)	OEL TWA (ppm)	100 ppm
Canada (British Columbia)	OEL STEL (ppm)	150 ppm
Canada (Ontario)	OEL TWA (ppm)	100 ppm
Canada (Ontario)	OEL STEL (ppm)	150 ppm

Per-Fix™ for Vinyl

according to the Hazardous Products Regulations (February 11, 2015)

Xylene (1330-20-7)		
USA (ACGIH)	ACGIH TWA (mg/m ³)	100 ppm
USA (ACGIH)	ACGIH Ceiling (mg/m ³)	150 ppm
Biological Exposure Index	Methylhippuric Acid in Urine (Post Shift), End of shift	1.5 g/g creatinine
Ethylbenzene (100-41-4)		
Canada (Alberta)	OEL TWA (ppm)	100 ppm
Canada (Alberta)	OEL TWA (mg/m ³)	434 mg/m ³
Canada (Alberta)	OEL Ceiling (ppm)	125 ppm
Canada (Alberta)	OEL Ceiling (mg/m ³)	543 mg/m ³
Canada (British Columbia)	OEL TWA (ppm)	20 ppm
Canada (Ontario)	OEL TWA (ppm)	20 ppm
Canada (Quebec)	VECD (ppm)	125 ppm
Canada (Quebec)	VECD (mg/m ³)	543 mg/m ³
Canada (Quebec)	VEMP (ppm)	100 ppm
Canada (Quebec)	VEMP (mg/m ³)	434 mg/m ³
USA (ACGIH)	ACGIH TWA (mg/m ³)	20 ppm
Biological Exposure Index	Sum of Mandelic Acid and Phenyl Glyoxylic Acid in Urine, End of shift at end of workweek	0.7 g/g creatinine
Methyl Acetate (79-20-9)		
Canada (Alberta)	OEL TWA (ppm)	200 ppm
Canada (Alberta)	OEL TWA (mg/m ³)	600 mg/m ³
Canada (Alberta)	OEL STEL (ppm)	250 ppm
Canada (Alberta)	OEL STEL (mg/m ³)	757 mg/m ³
Canada (British Columbia)	OEL TWA (ppm)	200 ppm
Canada (British Columbia)	OEL STEL (ppm)	250 ppm
Canada (Ontario)	OEL TWA (ppm)	200 ppm
Canada (Ontario)	OEL STEL (ppm)	250 ppm
Canada (Quebec)	VECD (ppm)	250 ppm
Canada (Quebec)	VECD (mg/m ³)	757 mg/m ³
Canada (Quebec)	VEMP (ppm)	200 ppm
Canada (Quebec)	VEMP (mg/m ³)	606 mg/m ³
USA (ACGIH)	ACGIH TWA (mg/m ³)	200 ppm
USA (ACGIH)	ACGIH Ceiling (mg/m ³)	250 ppm
Cumene (98-82-8)		
Canada (Alberta)	OEL TWA (ppm)	50 ppm
Canada (Alberta)	OEL TWA (mg/m ³)	246 mg/m ³
Canada (British Columbia)	OEL TWA (ppm)	25 ppm
Canada (British Columbia)	OEL STEL (ppm)	75 ppm
Canada (Ontario)	OEL TWA (ppm)	50 ppm
Canada (Quebec)	VEMP (ppm)	50 ppm
Canada (Quebec)	VEMP (mg/m ³)	246 mg/m ³
USA (ACGIH)	ACGIH TWA (mg/m ³)	50 ppm
1,2,4-Trimethyl Benzene (95-63-6)		
USA (ACGIH)	ACGIH TWA (mg/m ³)	25 ppm

8.2 Exposure Controls

Engineering Measures	: Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.
Personal Protective Equipment	
Eye / Face Protection	: Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.
Hand Protection	: Chemical-resistant gloves, tested according to EN 374.
Remarks	: Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to the place of work.
Skin and Body Protection	: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.
Respiratory Protection	: An approved respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits.



SAFETY DATA SHEET

Part No. See Section 1.1 (Liquid)

Print Date: 10/10/2019
Revision Date: 10/10/2019
Supersedes Date: 10/10/2019
Issue Date: 10/10/2019
Version: 1.0 (EN)-CA
Page: 7/12

Per-Fix™ for Vinyl

according to the Hazardous Products Regulations (February 11, 2015)

Compliance : If needed, wear an appropriate NIOSH approved respirator.
Other Protective Equipment : Safety showers and eye-wash stations should be available in the workplace near where the material will be used.
Environmental Exposure Controls : Avoid release to the environment.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical Properties

Boiling Point	> 56.90 °C	Melting / Freezing Point	> -98.00 °C
Flash Point, Liquid	> -20.00 °C		
Explosive Limits	LEL: 0.80 UEL: 24.60 vol %	Autoignition Temperature, Liquid	> 190.00 °C
Flammability	Highly Flammable Liquid	Density	0.879 g/cm ³
Molecular Weight	Not Available	Weight	7.335 lbs/gal
Vapor Pressure	Not Available	pH	Not Available
Vapor Density	Not Available	Evaporation Rate (nBac=1)	Not Available
Viscosity	Not Available	Partition Coefficient (Log Pow)	Not Available
Odor Threshold	Not Available	Refractive Index	Not Available
Physical State	Liquid	Heat Of Combustion	Not Available
Appearance / Color	Clear, Colourless	Water Solubility	Not Available
Odor	Paint-like	Decomposition Temperature	Not Available

9.2 Environmental Properties

Percent Volatile	90.89 % wt	VOC Regulatory	797.79 g/L (6.66 lbs/gal)
Percent VOC	89.45 % wt	VOC Actual	786.28 g/L (6.56 lbs/gal)
Percent HAP	44.58 % wt	HAP Content	391.86 g/L (3.27 lbs/gal)
Global Warming Potential	0.01 GWP	Maximum Incremental Reactivity	2.3460 g O3/g
Ozone Depletion Potential	0.00 ODP		

SECTION 10 - STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity : No specific test data related to reactivity is available for this products or its ingredients.

10.2 Chemical Stability

Chemical Stability : This product is stable.

10.3 Possibility of Hazardous Reactions

Hazardous Reactions : Under normal conditions of storage and use, hazardous reactions are not expected to occur.

10.4 Conditions to Avoid

Conditions to Avoid : Electrostatic Discharge, Other Ignition Sources, Hot Surfaces, Heat, Flames, Sparks, Strong Heating.

10.5 Incompatible Materials

Materials to Avoid : Strong Oxidizing Agents, Strong Reducing Agents, Alkali Metals, Strong Acids, Aluminum, Potassium t-Butoxide, Bases, Calcium Hypochlorite, Aluminum Chloride, Acids, Hydrogen Peroxide, Magnesium, Sulfuric Acid, Perchloric Acid, Nitrating Agents, Chlorosulfuric Acid, Potassium Chlorate, Heavy Metals and their Salts, Phenols, Performic Acid.

10.6 Hazardous Decomposition Products

Thermal Decomposition : Oxides of carbon, Aldehydes, Methanol, Acetic Acid, Peroxybenzoic Acid, Benzoic Acid.

SECTION 11 - TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological Effects

Per-Fix™ for Vinyl

according to the Hazardous Products Regulations (February 11, 2015)

Ethyl Acetate (CAS: 141-78-6 / EC: 205-500-4)

LD50 Oral (Rat)	5620 mg/kg (RTECS)
LD50 Dermal (Rabbit)	> 18000 mg/kg (Sigma-Aldrich)
LC50 Inhalation (Rat)	10600 ppm/4h (ChemInfo)

Methyl Ethyl Ketone (CAS: 78-93-3 / EC: 201-159-0)

LD50 Oral (Rat)	2737 mg/kg (Sigma-Aldrich)
LD50 Dermal (Rabbit)	6480 mg/kg (RTECS)
LC50 Inhalation (Rat)	205 mg/l/4h (ChemInfo)
LC50 Inhalation (Rat)	30200 ppm/4h (ChemInfo)

Toluene (CAS: 108-88-3 / EC: 203-625-9)

LD50 Oral (Rat)	> 2000 mg/kg (Lit.)
LD50 Dermal (Rabbit)	12124 mg/kg (IUCLID)
LC50 Inhalation (Rat)	> 20 mg/l/4h (Lit.)

Xylene (CAS: 1330-20-7 / EC: 215-535-7)

LD50 Oral (Rat)	4300 mg/kg (RTECS)
LD50 Dermal (Rabbit)	12126 mg/kg (Sigma-Aldrich)
LC50 Inhalation (Rat)	21.7 mg/l/4h (GESTIS Substance Database)
LC50 Inhalation (Rat)	6700 ppm/4h (ChemInfo)

Ethylbenzene (CAS: 100-41-4 / EC: 202-849-4)

LD50 Oral (Rat)	4720 mg/kg (ChemInfo)
LD50 Dermal (Rabbit)	15380 mg/kg (ChemInfo)
LC50 Inhalation (Rat)	17.2 mg/l/4h (IUCLID)
LC50 Inhalation (Rat)	4000 ppm/4h (ChemInfo)

Methyl Acetate (CAS: 79-20-9 / EC: 201-185-2)

LD50 Oral (Rat)	6970 mg/kg (Lit.)
LD50 Dermal (Rabbit)	> 5000 mg/kg (RTECS)
LC50 Inhalation (Rat)	> 49.28 mg/l/4h (External SDS)
LC50 Inhalation (Rat)	16000 - 32000 (ChemInfo)

Cumene (CAS: 98-82-8 / EC: 202-704-5)

LD50 Oral (Rat)	2900 mg/kg (RTECS)
LD50 Dermal (Rabbit)	10627 mg/kg (ChemInfo)
LC50 Inhalation (Rat)	40 mg/l/4h (ChemInfo)
LC50 Inhalation (Rat)	8000 ppm/4h (ChemInfo)

Light Aromatic Solvent Naphtha (CAS: 64742-95-6 / EC: 265-199-0)

LD50 Oral (Rat)	8400 mg/kg (RTECS)
LD50 Dermal (Rabbit)	> 3160 mg/kg (ChemInfo)
LC50 Inhalation (Rat)	3670 ppm/4h (Lit.)

1,2,4-Trimethyl Benzene (CAS: 95-63-6 / EC: 202-436-9)

LD50 Oral (Rat)	> 5000 mg/kg (RTECS)
LD50 Dermal (Rat)	> 3440 mg/kg (Lit.)
LC50 Inhalation (Rat)	18 mg/l/4h (RTECS)

Routes Of Exposure	: Eye Contact, Ingestion, Skin Contact, Inhalation, Skin Absorption.
Delayed and Immediate Effects and Also Chronic Effects from Short and Long Term Exposure	: See Section 4.2
Skin Corrosion/Irritation	: Causes skin irritation.
Eye Damage/Irritation	: Causes serious eye irritation.
Respiratory or Skin Sensitization	: Not classified
Germ Cell Mutagenicity	: May cause genetic defects.
Reproductive Toxicity	: Suspected of damaging fertility or the unborn child.
STOT-Single Exposure	: May cause drowsiness or dizziness.
STOT-Repeated Exposure	: May cause damage to organs through prolonged or repeated exposure.

Per-Fix™ for Vinyl

according to the Hazardous Products Regulations (February 11, 2015)

Aspiration Hazard
Carcinogen Data

: May be fatal if swallowed and enters airways.
 : The following ingredients are listed as known or suspected carcinogens:

Ethylbenzene (CAS: 100-41-4 / EC: 202-849-4)	
IARC group	2B - Possibly carcinogenic to humans
ACGIH Category	A3 - Confirmed animal carcinogen with unknown relevance to humans
Cumene (CAS: 98-82-8 / EC: 202-704-5)	
IARC group	2B - Possibly carcinogenic to humans

SECTION 12 - ECOLOGICAL INFORMATION

12.1 Ecotoxicity and Ecological Properties

Ethyl Acetate (141-78-6)	
LC50 Fish	450 - 600 mg/l Rainbow Trout - 96hr
LC50 Fish	220 - 250 mg/l Fathead Minnow - 96h
LC50 Other Aquatic Organisms	560 mg/l Water Flea - 48hr
EC50 Daphnia	2300 - 3090 mg/l Water Flea - 24hr
EC50 Other Aquatic Organisms	4300 mg/l Green Algae - 24hr
Persistence and Degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical Oxygen Demand	0.293 g O ₂ /g substance
Chemical Oxygen Demand	1.69 g O ₂ /g substance
Theoretical Oxygen Demand	1.82 g O ₂ /g substance
Biodegradation	100 % 28 Days
BCF Fish	30
Log Pow	0.73
Bioaccumulative Potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	0.778

Methyl Ethyl Ketone (78-93-3)	
LC50 Fish	3130 - 3320 mg/l Fathead Minnow - 96h
EC50 Daphnia	7060 mg/l Water Flea - 24hr
Persistence and Degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions.
Biochemical Oxygen Demand	2.03 g O ₂ /g substance
Chemical Oxygen Demand	2.31 g O ₂ /g substance
Theoretical Oxygen Demand	2.44 g O ₂ /g substance
Log Pow	0.3 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 40 °C)
Bioaccumulative Potential	Low potential for bioaccumulation (Log Kow < 4).
Log Koc	Koc,34; Calculated value

Toluene (108-88-3)	
LC50 Fish	5.8 mg/l Rainbow Trout - 96hr
LC50 Other Aquatic Organisms	10 mg/l Green Algae - 72hr
EC50 Daphnia	6 mg/l Water Flea - 48hr
Persistence and Degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for absorption in soil.
Biochemical Oxygen Demand	2.15 g O ₂ /g substance
Chemical Oxygen Demand	2.52 g O ₂ /g substance
Theoretical Oxygen Demand	3.13 g O ₂ /g substance
Biodegradation	86 % 28 Days
Log Pow	2.73 (Experimental Value)
Bioaccumulative Potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	2.15

Xylene (1330-20-7)	
LC50 Fish	26.7 mg/l Fathead Minnow - 96h
EC50 Daphnia	75.49 mg/l Water Flea - 48hr
EC50 Other Aquatic Organisms	72 mg/l Green Algae - 14d
Persistence and Degradability	Readily biodegradable in water.
Biochemical Oxygen Demand	1.40 - 2.53 g O ₂ /g substance
Chemical Oxygen Demand	2.56 - 2.91 g O ₂ /g substance
Theoretical Oxygen Demand	3.1 g O ₂ /g substance



SAFETY DATA SHEET

Part No. See Section 1.1 (Liquid)

Print Date: 10/10/2019
 Revision Date: 10/10/2019
 Supersedes Date: 10/10/2019
 Issue Date: 10/10/2019
 Version: 1.0 (EN)-CA
 Page: 10/12

Per-Fix™ for Vinyl

according to the Hazardous Products Regulations (February 11, 2015)

Xylene (1330-20-7)

BCF Fish	14.1 - 24 (BCF)
Log Pow	3.217
Bioaccumulative Potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	3.156

Ethylbenzene (100-41-4)

LC50 Fish	4.2 mg/l Rainbow Trout - 96hr
EC50 Daphnia	2.4 mg/l Water Flea - 48hr
EC50 Other Aquatic Organisms	9.68 mg/l Bacteria - 30min
EC50 Other Aquatic Organisms	4.6 mg/l Green Algae - 72hr
Persistence and Degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for absorption in soil.
Biochemical Oxygen Demand	1.44 g O ₂ /g substance
Chemical Oxygen Demand	2.1 g O ₂ /g substance
Theoretical Oxygen Demand	3.17 g O ₂ /g substance
Biodegradation	81 % 28 Days
BCF Fish	1.18
Log Pow	3.15
Bioaccumulative Potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	2.4

Methyl Acetate (79-20-9)

LC50 Fish	250 - 350 mg/l Zebra Fish - 96hr
EC50 Daphnia	1026.7 mg/l Water Flea - 48hr
EC50 Other Aquatic Organisms	> 120 mg/l Green Algae - 72hr
EC50 Other Aquatic Organisms	6100 mg/l Bacteria - 30min
Persistence and Degradability	Readily biodegradable in water. Inherently biodegradable. Highly mobile in soil.
Chemical Oxygen Demand	1511.8 mg/g
Theoretical Oxygen Demand	1510 mg/g
Biodegradation	70 % 28 Days
BCF Fish	< 1 (BCF)
Log Pow	0.18
Bioaccumulative Potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	0.68

Cumene (98-82-8)

LC50 Fish	4.8 mg/l Rainbow Trout - 96hr
EC50 Daphnia	2.14 mg/l Water Flea - 48hr
EC50 Other Aquatic Organisms	2.6 mg/l Green Algae - 72hr
Persistence and Degradability	Inherently biodegradable. Not readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical Oxygen Demand	1.28 g O ₂ /g substance
Chemical Oxygen Demand	2.42 g O ₂ /g substance
Theoretical Oxygen Demand	3.2 g O ₂ /g substance
Biodegradation	88 % 28 days
BCF Fish	35.5
BCF Other Aquatic Organisms	94.69
Log Pow	3.66
Bioaccumulative Potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	2.946

Light Aromatic Solvent Naphtha (64742-95-6)

LC50 Fish	18 mg/l (LC50)
EC50 Daphnia	21 mg/l (EC50)
Persistence and Degradability	Readily biodegradable in water.
Log Pow	> 3

1,2,4-Trimethyl Benzene (95-63-6)

LC50 Fish	7.72 mg/l Fathead Minnow - 96h
EC50 Daphnia	3.6 mg/l Water Flea - 48hr
Persistence and Degradability	Biodegradable in the soil. Not readily biodegradable in water.
Chemical Oxygen Demand	0.44 g O ₂ /g substance
BCF Fish	243 (Pimephales promelas, QSAR)

Per-Fix™ for Vinyl

according to the Hazardous Products Regulations (February 11, 2015)

1,2,4-Trimethyl Benzene (95-63-6)

Log Pow	3.63 (Experimental value, KOWWIN)
Bioaccumulative Potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	3.04 (log Koc, Calculated value)

SECTION 13 - DISPOSAL CONSIDERATIONS




13.1 Waste Treatment Methods

Waste Disposal	: Product is suitable for burning in an enclosed, controlled burner for fuel value. Hazard characteristics and regulatory waste stream classification can change with product use and location. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste material must be disposed of in compliance with the respective national, federal, state, and/or local regulations.
Waste Disposal Of Packaging	: Consult with your local landfill to determine if empty small containers can be disposed of along with regular trash pickup. For disposal of large containers (typically 10 gallons or larger), or for containers not suitable for landfill, a licensed reconditioner should be used.
Landfill Precautions	: Not Available.
Incineration Precautions	: Not Available.

SECTION 14 - TRANSPORTATION INFORMATION

14.1 UN Number	TDG (CANADA)	IATA (AIR)	IMDG (OCEAN)
UN Number	UN1263	UN1263	UN1263

14.2 UN Proper Shipping Name	TDG (CANADA)	IATA (AIR)	IMDG (OCEAN)
UN Proper Shipping Name	Paint	Paint	Paint

14.3 Transport Hazard Class(es)	TDG (CANADA)	IATA (AIR)	IMDG (OCEAN)
Transport Hazard Class(es)	3	3	3
Labels	3 - Flammable liquid 	3 - Flammable liquid 	3 - Flammable liquid 
EmS Code	Not Applicable	Not Applicable	F-E, S-E

14.4 Packing Group	TDG (CANADA)	IATA (AIR)	IMDG (OCEAN)
Packing Group	II	II	II

14.5 Environmental Hazards	TDG (CANADA)	IATA (AIR)	IMDG (OCEAN)
Marine Pollutant	No	No	No

14.6 Special Precautions	TDG (CANADA)
Precautions	: None Identified

14.7 Transport in Bulk	TDG (CANADA)
Remarks	: Not applicable for product as supplied

SECTION 15 - REGULATORY INFORMATION

15.1 Safety, Health and Environmental Regulations Specific to the Product

TSCA Inventory (United States)	: All chemical substances in this product are either listed on the Toxic Substances Control Act (TSCA) Inventory or are in compliance with a TSCA Inventory exemption.
DSL/NDL Inventory (Canada)	: All chemical substances in this product are listed on the Domestic Substance List (DSL), exempt or are not subject to notification.



SAFETY DATA SHEET

Part No. See Section 1.1 (Liquid)

Print Date: 10/10/2019
Revision Date: 10/10/2019
Supersedes Date: 10/10/2019
Issue Date: 10/10/2019
Version: 1.0 (EN)-CA
Page: 12/12

Per-Fix™ for Vinyl

according to the Hazardous Products Regulations (February 11, 2015)

SECTION 16 - OTHER INFORMATION

Indication of changes	:	Section	Changed item	Change
		1	Created Safety Data Sheet – Revision 1	Added

Full Text of H-Statements	:	H Code	H Phrase
		H225	Highly flammable liquid and vapour.
		H226	Flammable liquid and vapour.
		H304	May be fatal if swallowed and enters airways.
		H315	Causes skin irritation.
		H319	Causes serious eye irritation.
		H332	Harmful if inhaled.
		H335	May cause respiratory irritation.
		H336	May cause drowsiness or dizziness.
		H340	May cause genetic defects.
		H350	May cause cancer.
		H351	Suspected of causing cancer.
		H361	Suspected of damaging fertility or the unborn child.
		H373	May cause damage to organs through prolonged or repeated exposure.
		H401	Toxic to aquatic life
		H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects.		

Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.