

**Custom Oil - Hunter Satin**

**SECTION 1 - IDENTIFICATION**

**1.1 Product Identifier**

Product Name : *Custom Oil - Hunter Satin*  
 Manufacturer Product Number : *641-20*  
 Other Manufacturer Ids : *641-8 - INACTIVE*

**1.2 Other Means Of Identification**

Other Identifiers : *Not Available*

**1.3 Relevant Identified Uses Of The Substance Or Mixture And Uses Advised Against**

Recommended Use : *Gunstock finish*  
 Restrictions On Use : *None Identified*

**1.4 Supplier Details**

	Manufacturer Details	Supplier Details
Company Name	<i>Chem-Pak Inc</i>	<i>Chem-Pak Inc</i>
Address	<i>242 Corning Way, Martinsburg, WV 25405 - United States</i>	<i>242 Corning Way, Martinsburg, WV 25405 - United States</i>
Phone Number	<i>304-262-1880</i>	<i>304-262-1880</i>
Fax Number	<i>302-262-9643</i>	<i>302-262-9643</i>
Email	<i>msds@chem-pak.com</i>	
Website	<i>http://www.chem-pak.com</i>	

**1.5 24 Hr Emergency Phone Number**






Emergency Number : *800-255-3924 (Chem-Tel)*

**SECTION 2 - HAZARDS IDENTIFICATION**

**2.1 Classification Of The Substance Or Mixture**

Flammable Aerosols, Category 1 : *Extremely flammable aerosol*  
 Gases Under Pressure : Compressed Gas : *Contains gas under pressure; may explode if heated*  
 Skin Corrosion/Irritation, Category 2 : *Causes skin irritation*  
 Skin Sensitisation, Category 1 : *May cause an allergic skin reaction*  
 Carcinogenicity, Category 2 : *Suspected of causing cancer*  
 Reproductive Toxicity, Category 2 : *Suspected of damaging fertility or the unborn child*  
 Specific Target Organ Toxicity — Single Exposure, Category 3, Narcosis : *May cause drowsiness or dizziness*  
 Specific Target Organ Toxicity — Repeated Exposure, Category 2 : *May cause damage to organs through prolonged or repeated exposure*  
 Aspiration Hazard, Category 1 : *May be fatal if swallowed and enters airways*  
 Hazardous To The Aquatic Environment — Acute Hazard, Category 3 : *Harmful to aquatic life*  
 Hazardous To The Aquatic Environment — Chronic Hazard, Category 2 : *Toxic to aquatic life with long lasting effects*

**2.2 Label Elements**

Hazard Pictograms :     

GHS02      GHS04      GHS07      GHS08      GHS09

Signal Word : *Danger*



# SAFETY DATA SHEET

Part No. 641-20 Aerosol

Print Date: 05/18/2017

Revision Date: 05/18/2017

Version: 6.0 (EN)

Page 2 of 13

## Custom Oil - Hunter Satin

### Hazard Statements

: *Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life. Toxic to aquatic life with long lasting effects.*

### Precautionary Statements

: *Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves and eye protection. If swallowed: Immediately call POISON CENTER. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Call physician if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. Collect spillage. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container to local regulations.*

### 2.3 Other Hazards Which Do Not Result In Classification

Hazards Not Otherwise Classified : None Identified.

### 2.4 Unknown Acute Toxicity

41.66% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)  
 41.66% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)  
 16.66% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

## SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

### 3.1 Substance

Not Applicable

### 3.2 Mixture

Ingredient	Cas Number	%	Classification*
N-Hexane	110-54-3	30 - 60	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Propane	74-98-6	10 - 30	Flam. Gas 1, H220 Press. Gas (Diss.), H280
Hydrotreated Light Petroleum Distillate	64742-47-8	10 - 30	Asp. Tox. 1, H304
Xylene	1330-20-7	1 - 5	Flam. Liq. 2, H225 Aquatic Acute 2, H401
2-Butoxyethanol	111-76-2	1 - 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315
Ethyl Benzene	100-41-4	0.1 - 1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Zirconium 2-Ethylhexanoate	22464-99-9	0.1 - 1	Repr. 2, H361



# SAFETY DATA SHEET

Part No. 641-20 Aerosol

Print Date: 05/18/2017

Revision Date: 05/18/2017

Version: 6.0 (EN)

Page 3 of 13

## Custom Oil - Hunter Satin

Ingredient	Cas Number	%	Classification*
Methyl Ethyl Ketoxime	96-29-7	0.1 - 1	Flam. Liq. 4, H227 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351
Toluene	108-88-3	0.1 - 1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

## SECTION 4 - FIRST-AID MEASURES

### 4.1 Description Of First-Aid Measures

General Measures	: Call a physician immediately.
Eye Contact	: Rinse eyes with water as a precaution.
Skin Contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
Ingestion	: Do not induce vomiting. Call a physician immediately.
Inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-Aid Responder Protection	: Wear adequate personal protective equipment based on the nature and severity of the emergency.

### 4.2 Most Important Symptoms And Effects, Both Acute And Delayed

Eye Contact	: Liquid contact may cause pain along with moderate eye irritation.
Skin Contact	: Irritation. May cause an allergic skin reaction.
Ingestion	: Risk of lung oedema.
Inhalation	: Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion or death. Irritation of the mucous membranes, coughing, and dyspnea are also possible.

### 4.3 Indication Of Immediate Medical Attention And Special Treatment

Notes To Physician	: Treat symptomatically.
Specific Treatments/Antidotes	: No Information Available.
Immediate Medical Attention	: No Information Available.

## SECTION 5 - FIRE-FIGHTING MEASURES

### 5.1 Suitable Extinguishing Media

Extinguishing Media	: Water, carbon dioxide, dry chemical, universal aqueous film forming foam.
Unsuitable Media	: Water jet.

### 5.2 Specific Hazards Arising From The Chemical Or Mixture

Decomposition Products	: Decomposition products may include: oxides of nitrogen, vapors, oxides of carbon.
Hazards From The Product	: Extremely flammable. Contents under pressure. In a fire or if heated, a pressure increase will occur which may result in container bursting. Vapors heavier than air may spread along the ground and travel to ignition an source.



# SAFETY DATA SHEET

Part No. 641-20 Aerosol

Print Date: 05/18/2017

Revision Date: 05/18/2017

Version: 6.0 (EN)

Page 4 of 13

## Custom Oil - Hunter Satin

### 5.3 Special Protective Actions For Fire-Fighters

- Protective Actions** : Use water spray to cool fire exposed aerosol containers, as contents can rupture violently from heat developed pressure.
- Protective Equipment** : Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

### 6.1 Personal Precautions, Protective Equipment And Emergency Procedures

- For Non-Emergency Personnel** : No action should be taken involving any personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.
- For Emergency Responders** : Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel above.

### 6.2 Environmental Precautions

- Precautions** : Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

### 6.3 Methods And Materials For Containment And Cleaning Up

- Containment Procedures** : Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content may be contained with oil/solvent absorbent pads, socks, and/or absorbents.
- Cleanup Procedures** : Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.
- Other Information** : Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned.
- Prohibited Materials** : Combustible absorbent material such as sawdust. Use of equipment that may cause sparking.

## SECTION 7 - HANDLING AND STORAGE

### 7.1 Precautions For Safe Handling

- General Handling Precautions** : KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged or repeated skin contact. Avoid breathing of vapors. Do not incinerate (burn) containers. Always replace overcap when not in use. Avoid use around open flames or other sources of ignition. Exposure to heat or prolonged exposure to sun may cause can to burst. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation.
- Hygiene Recommendations** : Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

### 7.2 Conditions For Safe Storage Including Any Incompatibilities

- Storage Requirements** : Storage of individual cans should be done in an area below 55°C (120 °F), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended.
- Incompatibilities** : Segregate storage away from materials indicated in Section 10.
- NFPA 30B Classification** : This product is classified as a Level 3 Aerosol per NFPA 30B.

## SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control Parameters

Propane (74-98-6)		
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm



# SAFETY DATA SHEET

Part No. 641-20 Aerosol

Print Date: 05/18/2017

Revision Date: 05/18/2017

Version: 6.0 (EN)

Page 5 of 13

## Custom Oil - Hunter Satin

<b>Propane (74-98-6)</b>		
NIOSH	US IDLH (ppm)	2100 ppm
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
California	California PEL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	1000 ppm

<b>Xylene (1330-20-7)</b>		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
California	California PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	100 ppm
California	California PEL (STEL) (mg/m <sup>3</sup> )	655 mg/m <sup>3</sup>
California	California PEL (STEL) (ppm)	150 ppm
California	California PEL (Ceiling) (ppm)	300 ppm

<b>Ethyl Benzene (100-41-4)</b>		
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
NIOSH	US IDLH (ppm)	800 ppm
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	435
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	545 mg/m <sup>3</sup>
NIOSH	NIOSH REL (STEL) (ppm)	125 ppm
California	California PEL (TWA) (mg/m <sup>3</sup> )	22 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	5 ppm

<b>Toluene (108-88-3)</b>		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (ppm)	200
OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
NIOSH	US IDLH (ppm)	500 ppm
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
California	California PEL (TWA) (mg/m <sup>3</sup> )	37 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	10 ppm
California	California PEL (STEL) (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
California	California PEL (STEL) (ppm)	150 ppm
California	California PEL (Ceiling) (ppm)	500 ppm
BEI	Toluene in blood, Prior to last shift of workweek	0.02 mg/l
BEI	Toluene in urine, End of shift	0.03 mg/l
BEI	o-Cresol in urine (with hydrolysis), End of shift (B)	0.3 mg/g creatinine

<b>Zirconium 2-Ethylhexanoate (22464-99-9)</b>		
Not applicable		

<b>n-Hexane (110-54-3)</b>		
ACGIH	ACGIH TWA (ppm)	50 ppm



# SAFETY DATA SHEET

Part No. 641-20 Aerosol

Print Date: 05/18/2017

Revision Date: 05/18/2017

Version: 6.0 (EN)

Page 6 of 13

## Custom Oil - Hunter Satin

<b>n-Hexane (110-54-3)</b>		
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	500 ppm
NIOSH	US IDLH (ppm)	1100 ppm
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	180 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	50 ppm
California	California PEL (TWA) (mg/m <sup>3</sup> )	180 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	50 ppm
BEI	2,5-Hexanedion in urine (without hydrolysis), End of shift at end of workweek	0.4 mg/l

<b>2-Butoxyethanol (111-76-2)</b>		
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	240 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
NIOSH	US IDLH (ppm)	700 ppm
NIOSH	NIOSH REL (TWA) (ppm)	5 ppm
California	California PEL (TWA) (mg/m <sup>3</sup> )	97 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	20 ppm
BEI	Butoxyacetic Acid (BAA) in Urine, End of shift	200 mg/g creatinine

<b>Hydrotreated Light Petroleum Distillate (64742-47-8)</b>		
California	California PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Not applicable		

<b>Methyl Ethyl Ketoxime (96-29-7)</b>		
AIHA	WEEL TWA (ppm)	10 ppm

## 8.2 Exposure Controls

- Engineering Measures** : Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.
- Respiratory Protection** : An approved respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits. If respirators are needed, in the United States compliance with OSHA standard 29 CFR 1910.134 is necessary.
- Skin Protection** : For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.
- Eye/Face Protection** : Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.
- Other Protective Equipment** : Safety showers and eye-wash stations should be available in the workplace near where the material will be used.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Physical Properties

<b>Boiling Point</b>	> 68.70 °C	<b>Melting / Freezing Point</b>	> -96.00 °C
<b>Flash Point, Liquid</b>	-27.00 °C	<b>Flash Point, Propellant</b>	-104.40 °C
<b>Explosive Limits</b>	LEL: 0.60 UEL: 12.70 vol %	<b>Autoignition Temperature, Liquid</b>	205.00 °C
<b>Flammability</b>	Extremely Flammable Aerosol	<b>Density</b>	0.690 g/cm <sup>3</sup>
<b>Molecular Weight</b>	Not Available	<b>Weight</b>	5.758 lbs/gal
<b>Vapor Pressure</b>	Not Available	<b>pH</b>	Not Available



# SAFETY DATA SHEET

Part No. 641-20 Aerosol

Print Date: 05/18/2017

Revision Date: 05/18/2017

Version: 6.0 (EN)

Page 7 of 13

## Custom Oil - Hunter Satin

Vapor Density	Not Available	Evaporation Rate (nBac=1)	Not Available
Viscosity	Not Available	Partition Coefficient	Not Available
Odor Threshold	Not Available	Refractive Index	Not Available
Physical Form	Pressurized Product	Heat Of Combustion	15767.99 BTU/lb
Odor	Paint-like	Water Solubility	Not Available
Appearance / Color	Clear, Colorless	Decomposition Temperature	Not Available

### 9.2 Environmental Properties

Percent Volatile	81.26 % wt	VOC Regulatory	561.64 g/L (4.69 lbs/gal)
Percent VOC	63.69 % wt	VOC Actual	439.46 g/L (3.67 lbs/gal)
Percent HAP	4.62 % wt	HAP Content	31.88 g/L (0.27 lbs/gal)
Global Warming Potential	0.83 GWP	Maximum Incremental Reactivity	1.1670 g O3/g
Ozone Depletion Potential	0.00 ODP		

## SECTION 10 - STABILITY AND REACTIVITY

### 10.1 Reactivity

Reactivity : No specific test data related to reactivity is available for this products or its ingredients.

### 10.2 Chemical Stability

Stability : This product is stable.

### 10.3 Possibility Of Hazardous Reactions

Reactions : Under normal conditions of storage and use, hazardous reactions are not expected to occur.

### 10.4 Conditions To Avoid

Conditions : Electrostatic Discharge, Other Ignition Sources, Heat, Flames, Sparks.

### 10.5 Incompatible Materials

Incompatibilities : Strong Oxidizing Agents, Bases, Magnesium, Chlorosulfuric Acid, Chlorine, Potassium Chlorate, Dinitrogen Tetroxide, Chlorine Dioxide.

### 10.6 Hazardous Decomposition Products

Products : None identified.

## SECTION 11 - TOXICOLOGICAL INFORMATION

### 11.1.1 Information On Toxicological Effects

Propane (74-98-6)	
LC50 Inhalation (Rat)	658 mg/l/4h (Lit.)
Xylene (1330-20-7)	
LD50 Oral (Rat)	4300 mg/kg (RTECS)
LD50 Dermal (Rabbit)	12126 mg/kg (Sigma-Aldrich)
LC50 Inhalation (Rat)	6350 ppm/4h (ChemInfo)
Ethyl Benzene (100-41-4)	
LD50 Oral (Rat)	4720 mg/kg (ChemInfo)
LD50 Dermal (Rabbit)	15380 mg/kg (ChemInfo)
LC50 Inhalation (Rat)	17.2 mg/l/4h (IUCLID)
LC50 Inhalation (Rat)	4000 ppm/4h (ChemInfo)
Toluene (108-88-3)	
LD50 Oral (Rat)	> 2000 mg/kg (Lit.)
LD50 Dermal (Rabbit)	12124 mg/kg (IUCLID)
LC50 Inhalation (Rat)	> 20 mg/l/4h (Rat; Literature study)





# SAFETY DATA SHEET

Part No. 641-20 Aerosol

Print Date: 05/18/2017

Revision Date: 05/18/2017

Version: 6.0 (EN)

Page 8 of 13

## Custom Oil - Hunter Satin

### Zirconium 2-Ethylhexanoate (22464-99-9)

LD50 Oral (Rat)	> 5000 mg/kg (RTECS)
LD50 Dermal (Rabbit)	> 5000 mg/kg (RTECS)
LC50 Inhalation (Rat)	> 8800 mg/m <sup>3</sup> (RTECS)

### n-Hexane (110-54-3)

LD50 Oral (Rat)	29700 mg/kg (RTECS)
LD50 Dermal (Rabbit)	> 3350 mg/kg bodyweight (ChemInfo)
LC50 Inhalation (Rat)	38500 ppm/4h (ChemInfo)

### 2-Butoxyethanol (111-76-2)

LD50 Oral (Rat)	917 mg/kg (RTECS)
LD50 Dermal (Rabbit)	1060 mg/kg (Sigma-Aldrich)
LC50 Inhalation (Rat)	3380 mg/m <sup>3</sup> (RTECS)
LC50 Inhalation (Rat)	925 ppm/4h (ChemInfo)

### Hydrotreated Light Petroleum Distillate (64742-47-8)

LD50 Oral (Rat)	> 5000 mg/kg (ExxonMobil SDS)
LD50 Dermal (Rabbit)	> 5000 mg/kg (ExxonMobil SDS)
LC50 Inhalation (Rat)	> 5000 mg/kg (ExxonMobil SDS)

### Methyl Ethyl Ketoxime (96-29-7)

LD50 Oral (Rat)	> 930 mg/kg (RTECS)
LD50 Dermal (Rat)	> 2000 mg/kg (RTECS)
LD50 Dermal (Rabbit)	> 1000 mg/kg bodyweight (RTECS)
LC50 Inhalation (Rat)	20 mg/l/4h (Lit.)

## 11.1.2 Health Hazard Classification

Skin Corrosion/Irritation	: Causes skin irritation.
Eye Damage/Irritation	: Not classified
Respiratory Or Skin Sensitization	: May cause an allergic skin reaction.
Germ Cell Mutagenicity	: Not classified
Reproductive Toxicity	: Suspected of damaging fertility or the unborn child.
Stot-Single Exposure	: May cause drowsiness or dizziness.
Stot-Repeated Exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration Hazard	: May be fatal if swallowed and enters airways.
Carcinogen Data	: The following ingredients are listed as known or suspected carcinogens:

### Ethyl Benzene (100-41-4)

IARC group	2B - Possibly carcinogenic to humans
ACGIH Category	A3 - Confirmed animal carcinogen with unknown relevance to humans

### 2-Butoxyethanol (111-76-2)

ACGIH Category	A3 - Confirmed animal carcinogen with unknown relevance to humans
----------------	---

## 11.1.3 Information On The Likely Routes Of Exposure

Routes Of Exposure	: Eye Contact, Ingestion, Skin Contact, Inhalation, Skin Absorption.
--------------------	--

## 11.1.4 Symptoms Related To The Physical, Chemical And Toxicological Characteristics

Symptoms of Exposure	: Eye Irritation, Nose Irritation, Throat Irritation, Lassitude (Weakness), Dermatitis, Confusion, Skin Irritation, Headache, Dizziness, Nausea, Narcosis, Upper Respiratory Tract Irritation, Drowsiness, Vomiting, Cough, Chemical Pneumonitis (Aspiration Liquid), Numbness, Mucous Membrane.
----------------------	--

## 11.1.5 Delayed And Immediate Effects And Also Chronic Effects From Short And Long Term Exposure

Delayed Effects	: No known delayed effects.
Immediate Effects	: No known immediate effects.
Chronic Effects	: No chronic effects identified.





# SAFETY DATA SHEET

Part No. 641-20 Aerosol

Print Date: 05/18/2017

Revision Date: 05/18/2017

Version: 6.0 (EN)

Page 9 of 13

## Custom Oil - Hunter Satin

**Target Organs** : Blood, Central Nervous System, Eyes, Peripheral Nervous System, Respiratory System, Skin.  
**Medical Conditions Aggravated** : None identified.

## SECTION 12 - ECOLOGICAL INFORMATION

### 12.1 Ecotoxicity

**Ecology - general** : Toxic to aquatic life with long lasting effects. Harmful to aquatic life.

#### Xylene (1330-20-7)

LC50 fish 1	3.3 mg/l Rainbow Trout - 96hr
EC50 Daphnia 1	75.49 mg/l Water Flea - 48hr
EC50 other aquatic organisms 1	72 mg/l Green Algae - 14d

#### Ethyl Benzene (100-41-4)

LC50 fish 1	4.2 mg/l Rainbow Trout - 96hr
EC50 Daphnia 1	2.4 mg/l Water Flea - 48hr
EC50 other aquatic organisms 1	9.68 mg/l Bacteria - 30min
EC50 other aquatic organisms 2	4.6 mg/l Green Algae - 72hr

#### Toluene (108-88-3)

LC50 fish 1	5.8 mg/l Rainbow Trout - 96hr
LC50 other aquatic organisms 1	10 mg/l Green Algae - 72hr
EC50 Daphnia 1	6 mg/l Water Flea - 48hr

#### n-Hexane (110-54-3)

LC50 fish 1	2.5 mg/l Fathead Minnow - 96h
EC50 Daphnia 1	3878 mg/l Water Flea - 48hr

#### 2-Butoxyethanol (111-76-2)

LC50 fish 1	1490 mg/l Bluegill Sunfish - 96h
LC50 fish 2	1474 mg/l Rainbow Trout - 96hr
EC50 Daphnia 1	1698 - 1940 mg/l Water Flea - 24hr
EC50 other aquatic organisms 1	1840 mg/l Green Algae - 72hr

### 12.2 Ecological Properties

#### Propane (74-98-6)

Persistence and degradability	Readily biodegradable in water. Not applicable (gas). Photodegradation in the air.
BCF fish 1	9 - 25 (BCF)
Log Pow	2.28 (Calculated)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

#### Xylene (1330-20-7)

Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.40 - 2.53 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.56 - 2.91 g O <sub>2</sub> /g substance
ThOD	3.1 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.44 - 0.816
BCF fish 1	14.1 - 24 (BCF)
Log Pow	3.15 - 3.3
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

#### Ethyl Benzene (100-41-4)

Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	1.44 g O <sub>2</sub> /g substance (20d.)
Chemical oxygen demand (COD)	2.1 g O <sub>2</sub> /g substance
ThOD	3.17 g O <sub>2</sub> /g substance
BOD (% of ThOD)	45.4 (20 days)
BCF fish 1	1 (BCF; Other; 6 weeks; Oncorhynchus kisutch; Flow-through system; Salt water; Literature study)
BCF fish 2	15 - 79 (BCF)
BCF other aquatic organisms 1	4.68 (BCF)
Log Pow	3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	log Koc, PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value



# SAFETY DATA SHEET

Part No. 641-20 Aerosol

Print Date: 05/18/2017

Revision Date: 05/18/2017

Version: 6.0 (EN)

Page 10 of 13

## Custom Oil - Hunter Satin

<b>Toluene (108-88-3)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	2.15 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.52 g O <sub>2</sub> /g substance
ThOD	3.13 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.69
BCF fish 2	90 (BCF; 72 h; <i>Leuciscus idus</i> ; Static system; Fresh water)
Log Pow	2.73 (Experimental value; Other; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>n-Hexane (110-54-3)</b>	
ThOD	3.52 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.63 (Literature study)
BCF fish 1	501.187 (BCF; Other; <i>Pimephales promelas</i> )
Log Pow	3.9
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).
Log Koc	2.17
<b>2-Butoxyethanol (111-76-2)</b>	
Persistence and degradability	Biodegradability 90% / 28 days.
Biochemical oxygen demand (BOD)	0.71 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.2 g O <sub>2</sub> /g substance
ThOD	2.305 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.31
Log Pow	0.81 (Experimental value; BASF test; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Hydrotreated Light Petroleum Distillate (64742-47-8)</b>	
Persistence and degradability	Biodegradability 88% / 28 days.
Log Pow	6
<b>Methyl Ethyl Ketoxime (96-29-7)</b>	
BCF fish 1	0.5-5.8, BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 42 days; <i>Cyprinus carpio</i> ; Fresh water; Experimental value
Log Pow	0.63 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

## SECTION 13 - DISPOSAL CONSIDERATIONS





### 13.1 Waste Treatment Methods

- Waste Disposal** : Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of in compliance with the respective national, federal, state, and/or local regulations.
- Waste Disposal Of Packaging** : In the United States, an aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.
- Landfill Precautions** : Not Available.
- Incineration Precautions** : \*\* DO NOT INCINERATE \*\* CONTENTS UNDER PRESSURE \*\*.

## SECTION 14 - TRANSPORTATION INFORMATION

Transportation Information	Ground Transportation (DOT)	Air Transportation (IATA)	Ocean Transportation (IMDG)
Identification Number	UN1950	UN1950	UN1950
Proper Shipping Name	Aerosols, Limited Quantity	Aerosols, Flammable, Limited Quantity	Aerosols, Limited Quantity
Hazard Class(es)	2.1	2.1	2.1
Packaging Group	None	None	None
Limited Quantity	Yes	Yes	Yes

## Custom Oil - Hunter Satin

			
Marine Pollutant	No	No	No
Hazard Labels		2.1 - Flammable gas 	

## SECTION 15 - REGULATORY INFORMATION

### 15.1 Federal Regulations

#### Trace Ingredient Disclosure

: This product contains the following ingredients at a trace amount. These ingredients are known to the State of California to cause cancer.

Cumene CAS #98-82-8 -- 0.017724%

Quartz CAS #14808-60-7 -- 0.012%

#### TSCA Inventory

: All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

#### SARA 313 Reporting

: Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Xylene	CAS-No. 1330-20-7	1 - 5%
Ethyl Benzene	CAS-No. 100-41-4	< 1%
Toluene	CAS-No. 108-88-3	< 1%
Cumene	CAS-No. 98-82-8	< 1%
1,2,4-Trimethyl Benzene	CAS-No. 95-63-6	< 1%
n-Hexane	CAS-No. 110-54-3	30 - 60%

#### Applicable Federal Regulations

: One or more ingredients are regulated by other Federal Regulations.

#### Xylene (1330-20-7)

CERCLA RQ 100 lb

CWA Reportable Quantity 100 lb

RCRA Code U239

#### Ethyl Benzene (100-41-4)

CERCLA RQ 1000 lb

CWA Reportable Quantity 1000 lb

SARA Section 311/312 Hazard Classes Delayed (chronic) health hazard, Fire hazard, Immediate (acute) health hazard.

#### Toluene (108-88-3)

CERCLA RQ 1000 lb

#### n-Hexane (110-54-3)

CERCLA RQ 5000 lb

#### 2-Butoxyethanol (111-76-2)

SARA Section 311/312 Hazard Classes Delayed (chronic) health hazard, Fire hazard, Immediate (acute) health hazard.

### 15.2 State Regulations

#### California Proposition 65

: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

#### Ethyl Benzene (100-41-4)

Cancer Yes

No significant risk level (NSRL) 54



# SAFETY DATA SHEET

Part No. 641-20 Aerosol

Print Date: 05/18/2017

Revision Date: 05/18/2017

Version: 6.0 (EN)

Page 12 of 13

## Custom Oil - Hunter Satin

### Toluene (108-88-3)

Developmental Toxicity	Yes
No significant risk level (NSRL)	7000

#### State Right-to-Know Lists

: The following ingredients appear on one or more state Right-to-Know lists.

### Propane (74-98-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

### Xylene (1330-20-7)

U.S. - Massachusetts - Right To Know List  
 U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) List

### Ethyl Benzene (100-41-4)

U.S. - Massachusetts - Right To Know List  
 U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) List

### Toluene (108-88-3)

U.S. - Massachusetts - Right To Know List  
 U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) List

### n-Hexane (110-54-3)

U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) List

### 2-Butoxyethanol (111-76-2)

U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) List  
 U.S. - Massachusetts - Right To Know List

### Precipitated Silica (112926-00-8)

U.S. - New Jersey - Right to Know Hazardous Substance List

### 2-Phenoxyethanol (122-99-6)

U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16 - OTHER INFORMATION

#### SDS Compliance

: This SDS complies with the below listed regulations only. For SDS that comply with other countries, please contact our Regulatory Department at [msds@chem-pak.com](mailto:msds@chem-pak.com).

OSHA Hazard Communication Standard (HCS 2012) 29 CFR 1910.1200

Globally Harmonized System of Classification and Labeling of Chemicals (GHS) Revision 3

#### Disclaimer Of Liability

: The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.

#### Full text of H-statements

H Code	H Phrase
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways



# SAFETY DATA SHEET

Part No. 641-20 Aerosol

Print Date: 05/18/2017

Revision Date: 05/18/2017

Version: 6.0 (EN)

Page 13 of 13

## Custom Oil - Hunter Satin

H312	<i>Harmful in contact with skin</i>
H315	<i>Causes skin irritation</i>
H317	<i>May cause an allergic skin reaction</i>
H318	<i>Causes serious eye damage</i>
H332	<i>Harmful if inhaled</i>
H336	<i>May cause drowsiness or dizziness</i>
H351	<i>Suspected of causing cancer</i>
H361	<i>Suspected of damaging fertility or the unborn child</i>
H373	<i>May cause damage to organs through prolonged or repeated exposure</i>
H401	<i>Toxic to aquatic life</i>
H402	<i>Harmful to aquatic life</i>
H411	<i>Toxic to aquatic life with long lasting effects</i>